

Belt Conveyor



It an transport different weight goods, cartons, bags and other small pieces. The material of conveyor belt is metal (such as stainless), thus the strength is strong, scalability small, not easy deformation, easy maintenance, health, and can use in corrosion or bad environment sexual strong, long service life, and wide application.

NO.295,NORTH SONGWEI ROAD,SHANGHAI 201613,CHINA

Tel: +86-21-34662727 Fax:+86-21-34630350 E-mail:sales@tops-group.com



It is applicable to food, non-staple food, frozen aquatic products processing production lines, packing conveyor line and electronic parts of heating, baking, and also suitable for pharmaceutical, daily-life chemical and other industries.

Main features

- 6 belt width of conveyor: 500, 650, 800, 1000, 1200, 1400mm
- Frame structure: Stationary type, Mobile type
- Texture of belt: rubber belt, plastic belt, steel core belt, PVC belt, PU belt etc.
- Adopt corrosion resistant belt to convey reletive corrosive stuff, such as oil proof belt, anti-acid belt, alkali resisting belt.

Spec	cification	
Oper	Jinoution	

Belt width (mm) Belt	Dalt anad (m/a)	Conveying capacity (m ³ /h)		Motor Power
	Belt speed (m/s)	Groove type	Flat type	(kw)
500	0.8-2.5	78-232	41-125	1.5-30
650	0.8-2.5	131-391	67-211	1.5-40
800	1.0-3.15	278-824	118-350	1.5-75
1000	1.0-3.15	435-1233	230-546	3-100
1200	1.0-4.0	655-2202	345-821	4-185
1400	1.0-4.0	891-2996	469-1117	4-185

NO.295,NORTH SONGWEI ROAD,SHANGHAI 201613,CHINA

Tel: +86-21-34662727 Fax:+86-21-34630350 E-mail:sales@tops-group.com