

Rotary Auger Filling Machine



This series could do work of measuring, can holding, filling, weight chosen. It can constitute the whole set can filling work line with other related machines, and suitable for filling kohl, glitter powder, pepper, cayenne pepper, milk powder, rice flour, albumen powder, soy milk powder, coffee powder, medicine powder, essence and spice, etc.

Main features

- Easily to wash. Stainless steel structure, hopper can open.
- Stable and reliable performance. Servo-motor drives auger, Servo-motor controlled turntable with stable performance.
- Easy To Use Easily. PLC, touch screen and weighing module control.
- With pneumatic can lifting device to assure the material not spilling out when filling.
- Weight-chosen device, to assure each product be qualified, so to leave the latter cull eliminator.

NO.295,NORTH SONGWEI ROAD,SHANGHAI 201613,CHINA



- With adjustable height-adjustment hand wheel at reasonable height, easy to adjust the head position change.
- Save 20 sets of formula inside the machine for later use.
- Replacing the auger parts, different products ranging from fine powder to granule and different weight can be packed.
- Multi language interface.

Model	TP-PF-A31	TP-PF-A32
Container Size	Ф20-100mm;H15-150mm	Ф30-160mm;H50-260mm
Control system	PLC & Touch Screen	PLC & Touch Screen
Packing Weight	1 – 500g	10-5000g
Packing Accuracy	≤ 100g, ≤±2%; 100 – 500g, ≤±1%	≤ 500g, ≤±1%; >500g, ≤±0.5%
Filling Speed	20-50 bottles per min	20-40 bottles per min
Power Supply	3P AC208-415V 50/60Hz	3P AC208-415V 50/60Hz
Total Power	1.8 KW	2.3KW
Air Supply	6kg/cm2 0.05m3/min	6kg/cm2 0.05m3/min
Total Weight	250kg	350kg
Hopper	Quick disconnecting hopper 25L	Quick disconnecting hopper 50L
Overall Dimensions	1400×830×2080mm	1840×1070×2420mm



NO.295,NORTH SONGWEI ROAD,SHANGHAI 201613,CHINA

Tel: +86-21-34662727 Fax:+86-21-34630350 E-mail:sales@tops-group.com